

## [Sprinkler System and Water Spray System Devices] Valves, Trim and Drain

[See General Information for Sprinkler System and Water Spray System Devices](#)

### USE

This category covers trim and drain valves which consist of ball, plug, angle or globe type shutoff valves for use in air or water supply piping in conjunction with dry pipe, deluge or alarm valves on sprinkler systems. These valves are rated for a maximum pressure of 175 psi unless otherwise indicated in the individual Listings.

For additional information, see Sprinkler System and Water Spray System Devices ([VDGT](#)).

### REQUIREMENTS

The basic requirements used to investigate products in this category are specified in Subject 258, "Outline of Investigation for Shutoff Valves for Trim and Drain Purposes".

### UL MARK

The Listing Mark of Underwriters Laboratories Inc. on the product is the only method provided by UL to identify these products manufactured under its Listing and Follow-Up Service. The Listing Mark for these products includes the UL symbol (as illustrated in the Introduction of this Directory) together with the word "LISTED," a control number and one of the following product names, as appropriate: "Drain Valve," "Trim Valve" or "Trim and Drain Valve."

[Last Updated](#) on 2000-06-29

---

This page and all contents are Copyright © 2005 by Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2005 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



## Valves, Trim and Drain

[See General Information for Valves, Trim and Drain](#)

**V I R VALVOINDUSTRIA ING RIZZIO SPA**  
VIA CIRCONVALLAZIONE 10  
13018 VALDUGGIA, VC ITALY

EX6290

Model	Type	Size In.	Rated Pressure (psig)
Fig 340T	Ball	1/2, 3/4, 1	600
Fig 340T	Ball	1-1/4, 1-1/2 and 2	500
Fig 350T	Ball	1/4, 3/8, 1/2, 3/4, 1, 1-1/4	600
Fig 350T	Ball	1-1/2 and 2	550

[Last Updated](#) on 2002-07-13

This page and all contents are Copyright © 2005 by Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2005 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

