





VALVOLE A SFERA in PP e PP COPOLIMERO
PP and PP COPOLYMER BALL VALVES

| Codice famiglia | Caratteristiche | PN | Codice VIR | Dimensione mm - pollici | Pezzi per Scatola | Peso cad (g) | Peso per scatola (Kg) |
|-----------------|-----------------|----|------------|----------------------------|----------------------|--------------------|---------------------------|
| Family code | Specifications | PN | VIR code | Size inches | Pcs per Carton | Unit weight (g) | Weight per carton (Kg) |

| 220 | Valvola a sfera in PP | PN16 | F2200L008.247 | 008 - 1/4" | 100 | 66 | 7 |
|--|---|------|--|--------------|-----|------|---|
| | PP ball valve | | F2200L010.247 | 010 - 3/8" | 100 | 64 | 6 |
|  <p>Organo di manovra in nylon PA6 rinforzato vetro Sfera e asta in ottone Estremità filettate FF GAS, NPT o ISO7RC Guarnizioni in PTFE, O-ring in NBR Condizioni di esercizio: Acqua: da 0°C a +75°C</p> | | | F2200L015.247 | 015 - 1/2" | 50 | 83 | 4 |
| | | | F2200L020.247 | 020 - 3/4" | 40 | 125 | 5 |
| | | | F2200L025.247 | 025 - 1" | 25 | 256 | 6 |
| | | | F2200L032.247 | 032 - 1 1/4" | 15 | 389 | 6 |
| | | | F2200L040.247 | 040 - 1 1/2" | 10 | 671 | 7 |
| | | | F2200L050.247 | 050 - 2" | 6 | 1009 | 6 |
| | <p><i>Glass reinforced nylon PA6 handle Ball and stem in brass FF GAS, NPT or ISO7RC threaded ends PTFE seats, NBR O-ring Working conditions: Water: 0°C to +75°C</i></p> | | <p>A richiesta con sfera e perno in acciaio inox <i>Ball and stem in stainless steel on request</i></p> <p>Versione a farfalla disponibile allo stesso prezzo (1/4"-2") <i>Butterfly handle option at same price (1/4"-2")</i></p> | | | | |

| 228 | Valvola a sfera in PP copolimero | PN16 | F2280N015.496 | 015 - 1/2" | 50 | 82 | 4 |
|--|----------------------------------|------|--|------------|----|-----|---|
| | PP copolymer ball valve | | F2280N020.496 | 020 - 3/4" | 40 | 113 | 5 |
|  <p>Resistente al ghiaccio Organo di manovra in nylon PA6, sfera e asta in ottone Estremità filettate FF GAS, NPT o ISO7RC Guarnizioni in PTFE, O-ring in NBR Condizioni di esercizio: Acqua: da -20°C a +75°C</p> | | | F2280N025.496 | 025 - 1" | 25 | 232 | 6 |
| | | | <p><i>Ice-damaging resistant Glass reinforced nylon PA6 handle, ball and stem in brass FF GAS, NPT or ISO7RC threaded ends PTFE seats, NBR O-ring Working conditions: Water: -20°C to +75°C</i></p> | | | | |
| | | | <p>A richiesta con sfera e perno in acciaio inox <i>Ball and stem in stainless steel on request</i></p> <p>Versione a farfalla disponibile allo stesso prezzo (1/4"-1") <i>Butterfly handle option at same price (1/4"-1")</i></p> | | | | |