



Solid Lug rubber flexible joint  
For PN10 flanges according to EN1092-1/2  
(also suitable for PN16 flanges up to DN≤150)  
Steel threaded inserts  
TR CU 010 compliant

PN10/PN16  
Free of CE marking (cat. according to Art. 4.3 Dir. 2014/68/EU)

Working conditions

- Suitable for: water, -20°C to +100°C  
below 0°C only for water with added antifreeze fluids
- Not suitable for: gases group 1 & 2, liquids group 1 (Dir. 2014/68/UE)

## PARTLIST

N.	Part	Material	Norm
1	Body	EPDM	-
2	Threaded insert	Steel	-

## DIMENSIONS

DN	L [mm]	ØF [mm]	ØE [mm]	NxØD [mm]	Weight [kg]
020	70	108	75	4xM12	1,80
025	70	118	85	4xM12	2,40
032	70	143	100	4xM16	3,40
040	70	153	110	4xM16	3,90
050	70	168	125	4xM16	4,50
065	70	189	145	4xM16	5,50
080	70	204	160	8xM16	5,90
100	70	224	180	8xM16	7,50
125	70	254	210	8xM16	8,70
150	70	289	240	8xM20	11,10
200	90	344	295	12xM20	16,20

PN10

\*Version for PN10 flanges available on request



EAC

